



## **GMC POWERED SLIP ROLLS**

Model # [PSR-5016-1ph](#), 50" x 16Ga, 1.5 HP, 220V, 1 Phase.

Model# [PSR-5016](#), 50" x 16Ga, 1 HP, 220V/440V, 3 Phase.

Model # [PSR-5014](#), 50" x 14Ga, 1.5 HP, 220V/440V, 3 Phase.

### **Features:**

- [ISO 9001 certified](#)
- Heavy welded all steel construction for maximum rigidity
- Silence electrical motor
- Quick release top roller
- Two Powered driven Rolls
- Precision ground rollers
- 1" roll opening
- [All three rolls are made of high grade alloy steel, hardened up to 50 HRC](#)
- **Top & Bottom rolls run forward and reverse**
- Safety type removable foot pedal
- Overload protection and disconnect switch
- One year warranty for parts

### **Standard Equipment:**

- Electrical cabinet
- Removable safety foot pedal

Specifications	PSR-5016	PSR-5016-1ph	PSR-5014
Rolling capacity: mild steel	50" x 16 Ga.	50" x 16 Ga.	50" x 14Ga
stainless steel	50" x 20 Ga.	50" x 20 Ga.	50" x 18 Ga.
min. thickness capacity	50" x 22 Ga.	50" x 22 Ga.	50" x 22 Ga.
Rolls size, length x diameter	50" x 3"	50"x 3"	50"x 3"
Min. roll bending dia. capacity	3-1/2"	3-1/2"	50"x 3"
Rolls speed	201" / min.	201" / min.	201" / min.
Rolls opening	1/4"	1/4"1/4"	
(3) grooves sizes	5/16", 3/8", 1/2"	5/16", 3/8", 1/2"	5/16", 3/8", 1/2"
Main motor	1 HP,220V/440V, 3ph	1-1/2HP,220V, 1ph	1-1/2 HP,220V, 3ph
Net weight	828 LBS	828 LBS	928 LBS
Machine dimensions, LxWxH	68"x28"x47"	68"x28"x47"	68"x29"x48"

**Picture shown PSR-5016**

