

GMC DELUXE HYDRAULIC SHEARS

Model # HS-0410MD, 4' x 10 Ga, 5HP, 220V/440V, 3ph

Standard Features:

- ISO 9001 certified
- HD all steel construction for maximum rigidity
- German logic quiet hydraulic system
- **Adjustable stroke from 16-20 strokes per minute**
- **60" long squaring arm with inch / mm scale**
- **Work light with shadow line**
- spring hold-downs
- high grade carbon/chrome alloy steel blades and hardened to 62 hrc, 2-edge indexable upper blade and 4-edge indexable bottom blade
- Full length with full view finger guard
- Front supports and (2) side gauges
- Safety type foot pedal control
- Jog, single continuous auto operation modes
- One year warranty for parts

Standard Equipment for GMC Hydr. Shears MD series:

- **26" manual back gauge with inch/metric dual scale & one side operated hand wheel**
- **60" long squaring arm with inch / mm scale**
- 2 each 24" front support arms
- 2 each 14" Side gauges with inlaid inch/metric dual scale
- Work light
- Spring independent hold-downs
- full length finger guard
- Removable safety foot pedal control
- Tool box
- One set blades

Optional Equipment for GMC Hydr. Shears # HS-MD series:

- Safety fence for enclosure of the back side of the machine

Hydraulic Low Profile Deluxe Hydraulic Shear Specifications:

Specifications:				HS-0410MD	
Cutting capacity: mild steel stainless steel				4' x 10Ga. 4' x 14Ga.	
Blade length				52"	
Strokes per minute adjustable				16-20	
Throat depth				16"	
Worktable height				30-1/2"	
Front support arm				24"	
Back gauge				26" manual B.G.	
blade rake angle				1.5 degree	
oil tank cap.				15 Gal.	
Main motor				5-1/2 HP 220V/440V	
Machine weight				3,050 LBS	
Machine dimensions				68x35x52"	

