

GMC DELUXE HYDRAULIC SHEARS

Model# HS-0412MD , 4' x 12 Ga, 3HP, 220V/440V, 3ph

Standard Features:

- ISO 9001 certified
- HD all steel construction for maximum rigidity
- German logic quiet hydraulic system
- **Adjustable stroke from 16-20 strokes per minute**
- **60" long squaring arm with inch / mm scale**
- **Work light with shadow line**
- spring hold-downs
- high grade carbon/chrome alloy steel blades and hardened to 62 hrc, 2-edge indexable upper blade and 4-edge indexable bottom blade
- Full length with full view finger guard
- Front supports and (2) side gauges
- Safety type foot pedal control
- Jog, single continuous auto operation modes
- One year warranty for parts

Standard Equipment for GMC Hydr. Shears # HS-0412MD series:

- **26" manual back gauge with inch/metric dual scale & one side operated hand wheel**
- **60" long squaring arm with inch / mm scale**
- 2 each 24" front support arms
- 2 each 14" Side gauges with inlaid inch/metric dual scale
- Work light
- Spring independent hold-downs
- full length finger guard
- Removable safety foot pedal control
- Tool box
- One set blades

Optional Equipment for GMC Hydr. Shears # HS-0412MD series:

- Safety fence for enclosure of the back side of the machine

Hydraulic Low Profile Deluxe Hydraulic Shear Specifications:

Specifications:		HS-0412MD			
Cutting capacity: mild steel stainless steel		4' x 12 Ga. 4' x 16 Ga.			
Blade length		52"			
Strokes per minute adjustable		16-20			
Throat depth		16"			
Worktable height		30-1/2"			
Front support arm		24"			
Back gauge		26" manual B.G.			
blade rake angle		1.5 degree			
oil tank cap.		15Gal.			
Main motor		3 HP 220V/440V			
Machine weight		1,950 LBS			
Machine dimensions		68x33x51"			

