

GMC DELUXE HYDRAULIC SHEARS

Model # HS-0610MD, 6' x 10 Ga, 5HP, 220V/440V, 3 ph

Model # HS-0810MD, 8' x 10Ga., 7-1/2HP , 220V/440V, 3ph

Standard Features:

- **ISO 9001 certified**
- **HD all steel construction for maximum rigidity**
- **German logic quiet hydraulic system**
- **Adjustable stroke from 16-20 strokes per minute**
- **60" long squaring arm with inch / mm scale**
- **Work light with shadow line**
- **spring hold-downs**
- **high grade carbon/chrome alloy steel blades and hardened to 62 hrc, 2-edge indexable upper blade and 4-edge indexable bottom blade**
- **Full length with full view finger guard**
- **Front supports and (2) side gauges**
- **Safety type foot pedal control**
- **Jog, single continuous auto operation modes**
- **One year warranty for parts**

Standard Equipment for GMC Hydr. Shears # MD series:

- **26" manual back gauge with inch/metric dual scale & one side operated hand wheel**
- **60" long squaring arm with inch / mm scale**
- 2 each 24" front support arms
- 2 each 14" Side gauges with inlaid inch/metric dual scale
- Work light
- Spring independent hold-downs
- full length finger guard
- Removable safety foot pedal control
- Tool box
- One set blades

Optional Equipment for GMC Hydr. Shears # MD series:

- Safety fence for enclosure of the back side of the machine

Hydraulic Low Profile Deluxe Hydraulic Shear Specifications:

Specifications:					HS-0610MD	HS-0810MD
Cutting capacity: mild steel					6'x 10Ga	8'x10Ga
stainless steel					6'x 14Ga	8'x14Ga
Blade length					6'6"	8'2"
Strokes per minute adjustable					16-20	14-18
Throat depth					16"	16"
Worktable height					30-1/2"	30-1/2"
Front support arm					24"	24"
Back gauge					26" manual BG	
blade rake angle					1.5 degree	1.5 degree
oil tank cap.					20Gal.	20Gal.
Main motor					5-1/2HP	7-1/2HP 220V / 440V , 3 phase
Machine weight					4,150 LBS	5,650LBS
Machine dimensions					98x35x52"	118x35x52"



