



GMC DELUXE HYDRAULIC SHEARS

Model # HS-1010MD, 10' x 10 Ga, 7.5HP, 220V/440V, 3 phase

Model # HS-1014MD, 10' x 14 Ga, 5.5HP, 220V/440V, 3 phase

Standard Features:

- ISO 9001 certified
- HD all steel construction for maximum rigidity
- German logic quiet hydraulic system
- **Adjustable stroke from 16-20 strokes per minute**
- **60" long squaring arm with inch / mm scale**
- **Work light with shadow line**
- spring hold-downs
- high grade carbon/chrome alloy steel blades and hardened to 62 hrc, 2-edge indexable upper blade and 4-edge indexable bottom blade
- Full length with full view finger guard
- Front supports and (2) side gauges
- Safety type foot pedal control
- Jog, single continuous auto operation modes
- One year warranty for parts

Standard Equipment for GMC Hydr. Shears # HS-MD series:

- **26" manual back gauge with inch/metric dual scale & one side operated hand wheel**
- **60" long squaring arm with inch / mm scale**
- 2 each 24" front support arms
- 2 each 14" Side gauges with inlaid inch/metric dual scale
- Work light
- Spring independent hold-downs
- full length finger guard
- Removable safety foot pedal control
- Tool box
- One set blades

Optional Equipment for GMC Hydr. Shears # HS-MD series:

- Safety fence for enclosure of the back side of the machine

Hydraulic Low Profile Deluxe Hydraulic Shear Specifications:

Specifications:					HS-1010MD HS-1014MD
Cutting capacity: mild steel stainless steel					10' x 10 Ga 10' x 14Ga. 10' x 14 Ga 10' x 18 Ga
Blade length					10' 10'
Strokes per minute adjustable					14-18 14-18
Throat depth					16" 16"
Worktable height					30 -1/2" 30-1/2"
Front support arm					24" 24"
Back gauge					26" manual BG 26" manual BG 26" manual BG
blade rake angle					1.5 degree 1.5 degree
oil tank cap.					25 Gal. 20 Ga.
Main motor					7-1/2HP 5-1/2 HP 220V / 440V , 3 phase
Machine weight					6,350 LBS 5,200 LBS
Machine dimensions					139x35x52" 139x35x52



