



GMC HUDRAULIC SHOP PRESS

Model # HSP-30M, 30 ton, 3 HP, 220V, 3 phase.

Model # HSP-50M, 50 ton, 4 HP, 220V, 3 phase.

Model # HSP-100M, 100 ton, 4 HP, 220V, 3 phase.

Model # HSP-150M, 150 ton, 5 HP, 220V, 3 phase.

Model # HSP-200M, 200 ton, 7-1/2 HP, 220V, 3 phase.

Standard Features:

- **ISO 9001 certified & CE standard**
- **Electric hydraulic shop press**
- **Movable cylinder with hand wheel**
- **Rigid H frame**
- **Motorized and hand operation**
- **Fast and easy operation**
- **Automatic piston return**
- **Pressure gauge**
- **Overload protection and disconnect switch**
- **Power source 208V/220V, (Option 460 V , 3 phase)**
- **One year industrial warranty for parts**

Specifications				HSP-30M	HSP-50M	HSP-100M	HSP-150M	HSP-200M
Max. capacity				30 ton	50 ton	100 ton	150 ton	200 ton
Max. pressure				3625 PSI	4350 PSI	4350 PSI	4350 PSI	4350 PSI
Working speed				0.57 in /sec	0.17 in /sec	0.19 in /sec	0.19 in /sec	0.18 in /sec
Lowering speed				0.57 in /sec	0.85 in /sec	0.65 in /sec	0.65 in /sec	0.62 in /sec
Return speed				0.62 in /sec	0.90 in /sec	0.70 in /sec	0.70 in /sec	0.60 in /sec
Working width				19-1/2"	31"	38-1/2"	38-1/2"	38-1/2"
Movable cylinder				Yes	Yes	Yes	Yes	Yes
Cylinder stroke				11-3/4"	15-3/4"	15-3/4"	15-3/4"	15-3/4"
Cylinder Dia.				4-7/8"	5-1/2"	7-7/8"	7-7/8"	11-3/4"
Piston rod Dia.				2-1/2"	3-1/8	4	4	6
Piston head Dia.				2-1/2"	3-1/8	4	4	6
				2-1/16"		2-1/16"	2-1/16"	3/8"
Oil tank capacity				2 Gal.	16 Gal	32Gal.	32 Gal.	42 Gal.
Maim motor				3HP 220V, 3PH	4 HP 220V,3PH	4 HP 220V, 3PH	5 HP 220V, 3PH	7-1/2 HP 220V, 3PH
Mach Weight				1,050LBS	1,950 LBS	2,850 LBS	3,350 LBS	4,150 LBS
Dimensions, inch				53x23x67	65x26x79	69x30x89	69x31x89	79x34x89

